

Drainage washer HIDRO-Jet 150









Easy and efficient washing of drainage systems

A well-functioning drainage system improves the condition of arable land, an important prerequisite for high yields. In fields with a functioning drainage system, the plants germinate and grow evenly, allowing for the reduction of losses due to flooding of "wet places" and fields. A functioning drainage system is particularly needed for wet fields. Washing the drainage system with the HIDRO-JET/BI 300 is simple and safe - the powerful 300 m long washing pipe with hydraulic drive is used to insert the drainage well, a washer head with a 6 + 1 or 12 + 1 holes to clean the drain pipe from mud and plant roots. Adjustable hydraulic height and length of the unit, horizontal adjustment of the hydraulics for convenient and efficient operation of the equipment.

Technical data

Fastening	Three-point hitch
Hydraulics	
Hydraulic system	1 hydraulic motor
	1-section hydraulic divider
	1 flow control throttle
	Two-way connection

Pipe	
Washing pipe	150 m PPP pipe, Ø 27 mm x 5,5 mm
Sprayer head	Standard 12 + 1 hole or 6 + 1 hole of 2 mm, 2 mm
Meter counter	Serial
Pipe installation / pulling out	Hydraulic installation/pulling out
Weight	
Empty	~480 kg
Filled with water	~550 kg
Dimensions	1,10 m x 1,65 m x 2,05 m
Control	Hydraulic, with levers
Warranty	1 year